

POWERED BY **Dialog**

**Plastisol-like compsns. based on polyethylene (co)polymers - include reactive plasticiser component contg. long chain hydrocarbon residues**

**Patent Assignee:** HENKEL KGAA

**Inventors:** RITTER W; SCHAEFER M; TAUBER G

### Patent Family

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Type
DE 4435803	A1	19960411	DE 4435803	A	19941006	199620	B
WO 9611231	A2	19960418	WO 95EP3858	A	19950929	199621	
ZA 9508409	A	19960626	ZA 958409	A	19951005	199631	
WO 9611231	A3	19960613	WO 95EP3858	A	19950929	199633	

**Priority Applications (Number Kind Date):** DE 4435803 A ( 19941006)

**Cited Patents:** No search report pub.; EP 87344; FR 2018117; US 3988227; US 4130213

### Patent Details

Patent	Kind	Language	Page	Main IPC	Filing Notes
DE 4435803	A1		21	C08L-023/04	
WO 9611231	A2	G	35	C08L-023/04	
Designated States (National): BR CA CN CZ HU JP KR MX PL RU SI SK US					
Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LU MC NL PT SE					
ZA 9508409	A		42	C08L-000/00	
WO 9611231	A3			C08L-023/04	

### Abstract:

DE 4435803 A

A polymer-based mixt. having plastisol-like characteristics, comprising synthetic polymeric cpds. (I) as disperse phase mixed with a low molecular plasticiser component (II) that is liq. and/or solid at room temp. and which before heating the mixt. of (I) and (II) to film-forming temp. is a non-solvent for the polymer, and when heated to the film-forming temp. and above forms a storage-stable plastigel, whereby the (I) is chosen from polyethylene and copolymers of ethylene with propylene and/or adhesion-promoting comonomers chosen from low olefinically unsaturated acids, corresponding alcohols and/or their derivs.; and the plasticiser phase (II) consists of or contains reactive components which at temps. below the film-forming temp. are storage stable and non-solvents for the polymer phase and which at film-forming temps. are liq., and which upon raising the temp. at least to the plastigel-forming range, can react with an increase in the size of the mol., wherein the plasticiser components contain at least a predominant proportion of straight or branched chain 6-30 C hydrocarbon residues.

USE - Used as a replacement for PVC plastisols e.g. in the automobile ind., esp. as underbody protective coatings; as cable fillings and sealants; as interior and exterior coatings for tubes and pipelines; as adhesives for bonnet (hood) linings; as seals for vessel closures such as crown stoppers; as seam sealants in food packaging cans; as carpet backing materials; as coatings for textiles; as adhesive in laminated glass panes, etc.

ADVANTAGE - The components of the plastisol-like can be selected such that when heated to above the film forming temp., the reactive plasticiser components react e.g. by polymerisation to give a plastigel in the form of an interpenetrating polymer network (IPN) which can have excellent adhesion to the substrate. The gelled prods. have a good colour, good mechanical properties and a non-porous structure.

Dwg.0/0

Derwent World Patents Index

© 2005 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 10692408